Your distributor MANITOU:





MANITOU BF

Centre Logistique Pièces de Rechange

Rond Point de la Butte de Tir - BP 249 - 44158 Ancenis Cedex - France Tél. : 00 33 (0)2 72 50 40 00 - Fax : France : 00 33 (0)2 72 52 40 37 - Fax Export : 00 33 (0)2 72 52 40 47

www.manitou.com

This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specific actions shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 37,567,540 euros - 857 802 508 RCS Nantes

PALLET TRUCKS & HANDTRUCKS



Manual handling solutions





You benefit from the manual handling solutions best suited to your activity (transport, industry, construction, agriculture etc). Equipped with extremely strong chassis and forks, our products are designed to work under the most demanding conditions.

Improved ergonomics, safety and productivity.

All our products will meet the requirements of your daily activity and provide a high level of user comfort and manoeuvrability.

> **Essential** pallet truck!

Standard pallet truck

The widest possible range of uses!
Extremely strong and easy to manoeuvre, it's the market's "must have" pallet truck.

Standard model with ergonomic towing bar





- Easier to handle thanks to an ergonomic handle with a non-slip/cold-resistant coating.
- Simplified lifting and handling thanks to its 250 kg capacity hydraulic quick-lift system.
- > Simplified pallet handling thanks to the entry and exit rollers.

Standard model with park brake Ideal for use when lowering





Standard model with steel towing barEven stronger

TECHNICAL CHARACTERISTICS STANDAR

| TECHNICAL CHARACTERISTICS STANDARD | | | | | | | | | |
|------------------------------------|--------------|----------|-------------|---------------|------------------------|--------|-----------------|-----------|--|
| Description | Product code | Capacity | Fork length | Overall width | Fork height Min/Max | Weight | Rollers | Wheels | |
| Rubber single Roller | 787353 | 2500 kg | 1150 mm | 540 mm | 85/200 mm | 70 kg | Polyurethane x2 | Rubber x2 | |
| Rubber tandem roller | 787352 | 2500 kg | 1150 mm | 540 mm | 85/200 mm | 72 kg | Polyurethane x4 | Rubber x2 | |
| Steel towing bar tandem roller | 894423 | 2500 kg | 1150 mm | 540 mm | 85/200 mm | 65 kg | Polyurethane x4 | Rubber x2 | |
| Nylon single Roller | 787355 | 2500 kg | 1150 mm | 540 mm | 85/200 mm | 64 kg | Nylon x2 | Nylon x2 | |
| Nylon tandem roller | 787354 | 2500 kg | 1150 mm | 540 mm | 85/200 mm | 66 kg | Nylon x4 | Nylon x2 | |
| Handbrake - Tandem roller | 787356 | 2500 kg | 1150 mm | 540 mm | 85/200 mm | 73 kg | Polyurethane x4 | Rubber x2 | |

> **Special** pallet trucks suited to your activity!

Long forks







Ideal for handling in confined spaces (trucks, markets, paper mills, lifts etc.).

Compact, highly-manoeuvrable model equipped with short reinforced forks for handling small pallets.



High lift pallet truck

This ultra-ergonomic pallet truck adapts to the layout of workstations and allows the load to be levelled at the desired height.

- > Optimum operator working comfort with a raised position for facilitating loading and unloading of loads in total safety.
- > Automatic activation of stabilizers for stability and total safety for lifts in excess of 400mm.
- > No risk of leaks or loss of power with the selfcontained actuator.







Low forks

Essential for handling low loads.



Height of forks in lowered position 51 mm.





Perfect for handling large pallets



| TECHNICAL | CUADACTED | POLITOR |
|-------------|------------------|---------|
| ILCIIIVICAL | CHANACIL | แงแง |

| Description | Product code | Capacity | Fork length | Overall width | Fork height Min/Max | Weight | Rollers | Wheels |
|--------------------------------|--------------|----------|-------------|---------------|------------------------|--------|-----------------|-----------------|
| Long forks | | | | | | | | |
| 1800 mm - Tandem roller | 787363 | 1500 kg | 1800 mm | 540 mm | 85/200 mm | 81 kg | Polyurethane x4 | Rubber x2 |
| 1500 mm - Tandem roller | 787362 | 2000 kg | 1500 mm | 540 mm | 85/200 mm | 88 kg | Polyurethane x4 | Rubber x2 |
| Short forks | | | | | | | | |
| Single Roller | 787361 | 2500 kg | 800 mm | 540 mm | 85/200 mm | 65 kg | Polyurethane x2 | Rubber x2 |
| Tandem roller | 787360 | 2500 kg | 800 mm | 540 mm | 85/200 mm | 67 kg | Polyurethane x4 | Rubber x2 |
| Short & Narrow - Tandem roller | 787359 | 2000 kg | 800 mm | 450 mm | 85/200 mm | 65 kg | Polyurethane x4 | Rubber x2 |
| 900 mm - Tandem roller | 787357 | 2500 kg | 900 mm | 540 mm | 85/200 mm | 69 kg | Polyurethane x4 | Rubber x2 |
| Wide forks | | | | | | | | |
| Single Roller | 787368 | 2500 kg | 1150 mm | 685 mm | 85/200 mm | 72 kg | Polyurethane x2 | Rubber x2 |
| Tandem roller | 787367 | 2500 kg | 1150 mm | 685 mm | 85/200 mm | 75 kg | Polyurethane x4 | Rubber x2 |
| Low forks | | | | | | | | |
| Tandem roller | 787358 | 2000 kg | 1150 mm | 540 mm | 51/165 mm | 71 kg | Polyurethane x4 | Rubber x2 |
| High lift pallet truck | | | | | | | | |
| Manual | 720269 | 1000 kg | 1190 mm | 560 mm | 85/800 mm | 128 kg | Polyurethane x2 | Polyurethane x2 |
| Large (680 mm) - manual | 745112 | 1000 kg | 1190 mm | 680 mm | 85/800 mm | 133 kg | Polyurethane x2 | Polyurethane x2 |
| Electric | 720270 | 1000 kg | 1190 mm | 560 mm | 85/800 mm | 159 kg | Polyurethane x2 | Polyurethane x2 |
| Large (680 mm) - electric | 745183 | 1000 kg | 1190 mm | 680 mm | 85/800 mm | 164 kg | Polyurethane x2 | Polyurethane x2 |

> Pallet trucks for difficult environments, adapted to your circumstances!



Stainless steel pallet truck

Specially designed for environments with strict health requirements and corrosive or very damp environments (pharmaceutical sector, chemicals, agri-food, fisheries etc.).

- Optimum resistance to high temperatures and to chlorine and fluorine laden and marine environments thanks to a structure made entirely from type 316 stainless steel.
- > Usage temperature -40° to +40°.
- > Closed forks for a better hygiene
- > Lubrication and increased life thanks to the self-lubricating rings on the bogies.
- > Resistance to external agents, high pressure washes and detergents.





Galvanized pallet truck

Recommended for harsh, damp environments (agri-food, fishing industry etc.)

> Totally galvanized structure (fork carrier, pump, handle and forks) for improved strength.

TECHNICAL CHARACTERISTICS

| Description | Product code | Capacity | Fork length | Overall width | Fork height Min/Max | Weight | Rollers | Wheels | |
|------------------------------|--------------|----------|-------------|---------------|------------------------|--------|-----------------|-----------|--|
| Stainless steel pallet truck | | | | | | | | | |
| Tandem roller | 787366 | 2000 kg | 1150 mm | 540 mm | 85/200 mm | 71 kg | Nylon x4 | Nylon x2 | |
| Galvanized pallet truck | | | | | | | | | |
| Tandem roller | 787364 | 2000 kg | 1150 mm | 540 mm | 85/200 mm | 71 kg | Polyurethane x4 | Rubber x2 | |
| Tandem roller | 787365 | 2000 kg | 1150 mm | 540 mm | 85/200 mm | 71 kg | Nylon x4 | Nylon x2 | |



> Pallet truck for the demanding trades!

Weighing pallet truck

Essential for informing you quickly and easily of the weight of your loads when consigning or receiving them.







- Accuracy: 1kg/2T with 1 kg graduations; display accuracy 0.1%.
- > Easy to use: LCD screen, 18 mm digits, reset, tare and weight totalizing.
- LED battery charge state and paper level indicator.
- > Battery endurance 100 hrs.
- > Usage temperature -10°C to +40°C.
- > IP65 case protected against dust and water spray.

TECHNICAL CHARACTERISTICS

| Description | Product code | Capacity | Fork length | Overall width | Fork height Min/Max | Weight | Rollers | Wheels | |
|-----------------------|--------------|----------|-------------|---------------|------------------------|--------|-----------------|-----------|--|
| Weighing pallet truck | | | | | | | | | |
| Without printer | 744759 | 2000 kg | 1150 mm | 555 mm | 85/205 mm | 117 kg | Polyurethane x4 | Rubber x2 | |
| With printer | 744760 | 2000 kg | 1150 mm | 555 mm | 85/205 mm | 118 kg | Polyurethane x4 | Rubber x2 | |

Practical, lightweight strong trolleys!



► Light, folding mini hand truck

Ergonomic and easy to handle. Fully foldable and takes up little space; it can be easily housed inside a vehicle. Aluminium model.

Dimensions

- > unfolded: 410 x 400 x 1100 mm.
- > folded: 200 x 400 x 750 mm.
- > Max load: 90 kg.
- > Solid wheels: Ø 150 mm.





▶ Dual purpose hand truck

Dual-purpose: truck and trolley. Very easy to handle, using the frame or the handles.

Aluminium model.

Dimension

- > As hand truck: 520 x 470 x 1310 mm.
- > As trolley: 520 x 1190 x 1030 mm. Max load:
- > As hand truck: 200 kg.
- > As trolley: 300 kg.
- > Inflatable tyres: Ø 260 mm.



Heavy duty hand truck

Very strong thanks to its reinforced plate. Aluminium model.»

- > Dimensions: 420 x 510 x 1330 mm.
- > Max load: 300 kg.
- > Semi-inflatable tyres: Ø 250 mm.





► Hand truck

The classic truck for everyday handling tasks. Standard model made from high strength steel.

- > Height: 1232 mm
- > Width: 536 mm
- > Max load: 250 kg



